



## REG-0526 — Regulatory provisions for Minimum-Pair separations based on RSP (Required Surveillance Performance)

*Regulatory provisions (produced by the competent regulatory authority) that relate to the minimum of separation minima to apply to cope with surveillance performance. These regulatory provisions consists in defining minimum requirements for allowing 2.0NM minimum radar separation for both arrivals and departures operations.*

*"Regulatory provisions" refers here to advice from the regulatory authorities on the acceptability of a safety case supporting an ATM rule modification.*

**Category** INSTITUTIONAL


**Sub Category**

**Stakeholder** Unassigned

**Publication Date** 31-12-2018

### Context

#### Related Elements



**OI** Operational Improvement Steps: No associated data

**EN** Dependent Enablers

Relationship	Code	Title	Related Elements
Enabling	APP ATC 159	Approach ATC system updated for Minimum Separation Based on Required Surveillance Performance (separation delivery)	<b>STK</b> <b>OI</b> <b>EN</b> <b>DS</b>
Enabling	PRO-257	ATC Procedure to apply spacing minimum down to 2 NM	<b>STK</b> <b>OI</b> <b>EN</b> <b>DS</b>

**PCP** PCP Elements: No associated data

**STK** Stakeholders: No associated data

 Standards: No associated data

**OBJ** Implementation Objectives: No associated data

Stakeholder Lines of Action (SLoAs): No associated data

**PJ** SESAR Workpackages: No associated data